

VIBRATION ISOLATORS



TAPER MOUNT



UNIVERSAL MOUNT

► **FEATURES AND BENEFITS**

- Improves ground clearance by nearly 2 inches over existing solutions
- Weight savings of nearly 10 pounds over existing solutions
- Improves image stability through vibration dampening
- Built-in taper assembly or universal mounting plate compatible with existing mounts & bolt patterns
- Gimbal mounting hardware is accessible without vibration isolator disassembly
- Captured ¼-28 gimbal mounting hardware included

► **SPECIFICATIONS**

Diameter: 16 inches (40.64 cm.)

Height: 2.5 inches (6.35 cm.)

Weight: 10.3 lbs. (4.67 kg.)

► **GSS ISOLATOR SPRING CONFIGURATIONS**

GSS P/N	Mounting Configuration	Spring Configuration	Spring P/N	Cinema Mini/ Cineflex 512	Cinema Mini/ Cineflex Pro 512EX	Cinema Pro/ Cineflex Pro+ 516	Cinema Pro+ 520		
				<60 lbs <27.22 kg	60-70 lbs 27.22-31.75 kg	70-95 lbs 31.75-45.36 kg	120 lbs 54.43 kg	135 lbs 61.23 kg	150 lbs 68.04 kg
A1170-1	Taper Mount	400 Springs	M3-110-10					X	X
A1170-2	Taper Mount	600 Springs	M3-130-10		X	X	X	X	
A1170-3	Taper Mount	700 Springs	M3-140-10	X					
A1178-1	Universal Mount	400 Springs	M3-110-10					X	X
A1178-2	Universal Mount	600 Springs	M3-130-10		X	X	X	X	
A1178-3	Universal Mount	700 Springs	M3-140-10	X					